

# Stock for resistance wire

Range of alloys from our stock

DIN EN	Material	DIN	according to DIN
1.4860	VDM® Alloy HT 30	NiCr 3020	17470
2.4867	VDM® Alloy HT 60	NiCr 6015	17470 / 17471
2.4869	VDM® Alloy HT 80	NiCr 8020	17470 / 17471
2.0842	VDM Konstantan®	CuNi 44	17471 / 17664 / 46464

as of April 2023

Round wire in 0.05 mm steps

Format	Delivery form	according to DIN
0.10 – 1.50 mm	auf Spulen	46399
0.40 – 1.50 mm	in Fässern	46396
> 1.50 mm	in Ringen	

as of April 2023

Rolling wire to flat wire

Format	Delivery form	according to DIN
0.08 – 1.50 mm x 0.40 – 5.50 mm	auf Spulen	46399

as of April 2023

## Our service

### Tailor-made solutions at any time

- Heating elements and wire wound resistors for electric furnaces can be functionally designed and manufactured to your specifications at a short notice.
- Delivery with test certification 3.1

For your demand of further materials and dimensions, that are not specified in the list, we offer you the possibility to manufacture those items to your specific requirements, to provide storage in our Service Center as well as to provide the goods in partial deliveries.

Please find further information about processing our alloys and material data sheets online on our website: [www.vdm-metals.com](http://www.vdm-metals.com)

## Your key benefits

- Package business
- Rolling wire to flat wire
- Time saving by fast and flexible handling
- Technical know-how and material recommendations by our application engineers
- 24-hours delivery service (for stock products)